DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²



General data

The power cable UK BS1363A - C13 180°, 10 A, black from EFB-Elektronik is designed for use in UK applications and connects a BS1363A plug to an IEC socket. With a length of 2.0 m, a black outer jacket and a standard-compliant design, it is suitable for flexible power supplies in technical systems.

- Version with BS1363A connection and IEC socket for UK appliance connections
- 2.0 m length with black PVC sheath for practical integration
- 3-wire cable with protective conductor for a safe power supply up to 10 A

The 90° angle design at port 1 and straight port 2 supports space-saving cable routing. The material polyvinyl chloride (PVC) and the operating temperature range of 0 to 70 °C make the power cable suitable for typical installation environments. With a nominal voltage of 250 V and a nominal current of 10 A, it is designed to supply corresponding consumers.

Technical details
- Brand: EFB-Elektronik
- Country suitability: UK
- Port 1: BS1363A
- Connector 1 angle: 90°

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²

- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

Technical properties	
Bending radius (dynamic/static)	71 mm
Cable printing	H05VV-F 3G 1.00mm² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 1.00mm² MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK484.2	Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²	black	2.0 m	10 A	250 V	Dca	1.0 mm²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION