DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²

General data

The power cable UK BS1363A - C13 180°, 10 A, black from EFB-Elektronik is designed for use in UK applications and connects a BS1363A plug to an IEC socket. With a length of 2.0 m, a black outer jacket and a standard-compliant design, it is suitable for flexible power supplies in technical systems.

- Version with BS1363A connection and IEC socket for UK appliance connections
- 2.0 m length with black PVC sheath for practical integration
- 3-wire cable with protective conductor for a safe power supply up to 10 A

The 90° angle design at port 1 and straight port 2 supports space-saving cable routing. The material polyvinyl chloride (PVC) and the operating temperature range of 0 to 70 °C make the power cable suitable for typical installation environments. With a nominal voltage of 250 V and a nominal current of 10 A, it is designed to supply corresponding consumers.

Technical details
- Brand: EFB-Elektronik
- Country suitability: UK
- Port 1: BS1363A
- Connector 1 angle: 90°

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²

- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

Technical properties	
Bending radius (dynamic/static)	71 mm
Cable printing	H05VV-F 3G 1.00mm² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 1.00mm² MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK484.2	Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 1.00 mm²	black	2.0 m	10 A	250 V	Dca	1.0 mm²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION