DATASHEET

Power Cable South Africa - C13, 1.8 m, Black, 3 x 0.75 mm²



General data

The South Africa C13 1.8 m power cable from EFB-Elektronik is designed as a 3-wire connection cable for use in South Africa. With a Type M angled connection and a straight IEC socket, it is suitable for space-saving device connections in technical applications.

• Type M angled with 90° and IEC socket straight with 180°
• Black PVC outer jacket with protective conductor and 250 V nominal voltage

The material polyvinyl chloride supports robust and practical cable routing for daily use. The temperature range of 5 to 70 °C and the 3-wire design with protective conductor take into account typical requirements in electrical connections where a compact and resilient power cable is required.

Technical details
• Brand: EFB-Elektronik
• Core Count: 3
• Connector 1: Type M angled
• Connector 1 angle: 90°
• Connection 2: IEC socket straight
• Connector 2 angle: 180°
• Outer jacket colour: black
• Operating temperature: 5 – 70 °C
• Sheath material: Polyvinyl chloride (PVC)
• Nominal voltage: 250 V
• Protective conductor available
• Country suitability: South Africa

Technical properties

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable South Africa - C13, 1.8 m, Black, 3 x 0.75 mm²

Colour outer sheath	black
Connection 1	Typ M angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	South-Africa
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	5 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Spiralized cable	False
Storage Temperature	5 – 70 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal voltage	Nominal cross section conductor
EK488.1,8V2	Power Cable South Africa - C13, 1.8 m, Black, 3 x 0.75 mm²	black	IP20	1.8 m	250 V	0.75 mm²

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION