DATASHEET

Power Cable China Type I - C13 180°, Black, 1.8 m, 3 x 0.75 mm²



General data

The China Type I C13 180° black power cable from EFB-Elektronik is designed as a practical connection cable for use in China. With Type I China as port 1 and an IEC socket as port 2, it supports standard-level network connections with a length of 1.8 m.

- Black finish for unobtrusive integration into technical environments
- Port 1 as Type I China with 180° angulation
- Connection 2 as an IEC socket with 180° angulation

The polyvinyl chloride (PVC) sheath material supports a robust and at the same time practical design for daily use. The line is specified with three wires, protective conductors, a nominal voltage of 220 V and a nominal current of 10 A. This provides a clearly defined power cable for common applications with suitable mechanical and electrical design.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Type I China
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable China Type I - C13 180°, Black, 1.8 m, 3 x 0.75 mm²

- Outer jacket colour: black
- Country suitability: China
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 220 V
- Rated current: 10 A
- Protective conductor available

Technical properties	
Cable printing	CCC A019343 60227 IEC 53(RVV) 3*0.75mm² 300/500V□□ □□□□□□□□ 2007010105249975
Colour outer sheath	black
Connection 1	Typ I China
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	China
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	
Plug imprint	C3-10 CCC A019343 250V 10A
Protective conductor	True
Security certificates	CCC
Spiralized cable	False
Storage Temperature	
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable China Type I - C13 180°, Black, 1.8 m, 3 x 0.75 mm²

EK492.1,8V2	Power Cable China Type I - C13 180°, Black, 1.8 m, 3 x 0.75 mm²	black	IP20	1.8 m	10 A	220 V	0.75 mm²	6.5 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION