

DATASHEET

Power Cable Australia - C13 180°, Black, 1.8 m, 3 x 0.75 mm²



General data

The power cable Australia AS3112 - C13 180°, black from EFB-Elektronik is designed for use in Australia and connects a Type I Australia connection with an IEC socket. With a length of 1.8 m, it is suitable for compact and practical power connections in various technical environments.

- Version in black outer jacket colour
- Suitable for Australia with Type I Australia on port 1

The 3-core, PVC-jacketed and protective conductor design supports a robust power supply solution for device connections in the 250 V at 10 A voltage range. The operating temperature range of 0 to 70 °C describes the intended scope of use for typical installations and applications.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Port 1: Type I Australia
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

Power Cable Australia - C13 180°, Black, 1.8 m, 3 x 0.75 mm²

- Outer jacket colour: black
- Country suitability: Australia
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

Technical properties

Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm ² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	Typ I Australia
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Australia
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

Power Cable Australia - C13 180°, Black, 1.8 m, 3 x 0.75 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK493.1,8	Power Cable Australia - C13 180°, Black, 1.8 m, 3 x 0.75 mm ²	black	1.8 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.

