
DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C







General data

The NEMA 5 15 Plug C5 1.8 m power cord from EFB-Elektronik is designed for use in the USA and connects a NEMA 5-15 plug with a C5 cloverleaf coupling in 180° design. The black cable with 3 wires and protective conductor is suitable for standard-compliant power supplies in compact installations.

- Connection combination of NEMA 5-15 connector and C5 cloverleaf coupling, each at 180° angle
- Black version for use in the USA
- 3-wire power cable with protective conductor, designed for 125 V and 7 A

The polyvinyl chloride (PVC) jacket supports a practical design for technical applications in the intended temperature range of 0 to 70 °C. With a nominal voltage of 125 V and a current rating of 7 A, the cable is designed to provide a clear, application-specific specification.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: NEMA 5-15 connector
- Connector 1 angle: 180°
- Port 2: C5 cloverleaf coupling

This datasheet was created automatically on 13-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C

- Connector 2 angle: 180°
- Outer jacket colour: black
- Operating temperature: 0 – 70 °C
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 125 V
- Rated current: 7 A
- Protective conductor available
- Country suitability: USA

Technical properties	
Bending radius (dynamic/static)	63 mm
Cable printing	(UL) SVT 3/C 18AWG(0.824mm²) VW-1 75°C 300V E204978 C(UL) SVT 3/C 0.824MM² (18AWG) FT2 60°C 300V E204978
Colour outer sheath	black
Connection 1	NEMA 5-15 plug
Connection 2	C5 Mickey Mouse female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	USA
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	125 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	UL
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 13-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK497.1,8	Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C	black	1.8 m	7 A	125 V	Dca	0.83 mm²	6.3 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION