

DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C



General data

The NEMA 5 15 Plug C5 1.8 m power cord from EFB-Elektronik is designed for use in the USA and connects a NEMA 5-15 plug with a C5 cloverleaf coupling in 180° design. The black cable with 3 wires and protective conductor is suitable for standard-compliant power supplies in compact installations.

- Connection combination of NEMA 5-15 connector and C5 cloverleaf coupling, each at 180° angle
- Black version for use in the USA
- 3-wire power cable with protective conductor, designed for 125 V and 7 A

The polyvinyl chloride (PVC) jacket supports a practical design for technical applications in the intended temperature range of 0 to 70 °C. With a nominal voltage of 125 V and a current rating of 7 A, the cable is designed to provide a clear, application-specific specification.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: NEMA 5-15 connector
- Connector 1 angle: 180°
- Port 2: C5 cloverleaf coupling

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C

- Connector 2 angle: 180°
- Outer jacket colour: black
- Operating temperature: 0 – 70 °C
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 125 V
- Rated current: 7 A
- Protective conductor available
- Country suitability: USA

Technical properties	
Bending radius (dynamic/static)	63 mm
Cable printing	(UL) SVT 3/C 18AWG(0.824mm ²) VW-1 75°C 300V E204978 C(UL) SVT 3/C 0.824MM ² (18AWG) FT2 60°C 300V E204978
Colour outer sheath	black
Connection 1	NEMA 5-15 plug
Connection 2	C5 Mickey Mouse female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	USA
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	125 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	UL
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK497.1,8	Power Cable USA/NEMA 5-15P - C5 180°, Black, 1.8 m, SVT AWG18 x 3C	black	1.8 m	7 A	125 V	Dca	0.83 mm ²	6.3 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

