


DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²



General data

The UK BS1363A - C7 180° power cable, black from EFB-Elektronik is designed as a 1.8 m long power cable for use in Great Britain. With BS1363A connector at 90° angle and C7 coupling 180°, it is suitable for compact, standard-compliant power connections in various applications.

- 1.8 m length for flexible connection paths
- BS1363A connector 1 with 90° angulation and C7 coupling 180°
- Black version for use in the UK

The polyvinyl chloride (PVC) sheath material supports a robust and at the same time practical design for technical applications. The design for 250 V, 2.5 A and an operating temperature range of 0 - 70 °C complements the suitability for common mains connections. The existing protective conductor increases compliance for corresponding applications.

Technical details

- Brand: EFB-Elektronik
- Core Count: 2
- Port 1: BS1363A
- Connector 1 angle: 90°
- Connector 2: C7 coupling 180°

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²

- Connector 2 angle: 180°
- Outer jacket colour: black
- Country suitability: UK
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 2.5 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

Technical properties

Bending radius (dynamic/static)	57 mm
Cable printing	D S N FI OVE KEMA-KEUR IEMMEQU VDE N20050 H03VVH2-F 2x0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	C7 plug female 180°
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	2
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK498.1,8	Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm ²	black	1.8 m	2.5 A	250 V	Dca	0.75 mm ²	3.5 x 5.7 mm
EK498.3	Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm ²	black	3.0 m	2.5 A	250 V	Dca	0.75 mm ²	3.5 x 5.7 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.

