
DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²







General data

The UK BS1363A - C7 180° power cable, black from EFB-Elektronik is designed as a 1.8 m long power cable for use in Great Britain. With BS1363A connector at 90° angle and C7 coupling 180°, it is suitable for compact, standard-compliant power connections in various applications.

- 1.8 m length for flexible connection paths
- BS1363A connector 1 with 90° angulation and C7 coupling 180°
- Black version for use in the UK

The polyvinyl chloride (PVC) sheath material supports a robust and at the same time practical design for technical applications. The design for 250 V, 2.5 A and an operating temperature range of 0 – 70 °C complements the suitability for common mains connections. The existing protective conductor increases compliance for corresponding applications.

Technical details
- Brand: EFB-Elektronik
- Core Count: 2
- Port 1: BS1363A
- Connector 1 angle: 90°
- Connector 2: C7 coupling 180°

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²

- Connector 2 angle: 180°
- Outer jacket colour: black
- Country suitability: UK
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 2.5 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

Technical properties	
Bending radius (dynamic/static)	57 mm
Cable printing	D S N FI OVE KEMA-KEUR IEMMEQU VDE N20050 H03VVH2-F 2x0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	C7 plug female 180°
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	2
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK498.1,8	Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²	black	1.8 m	2.5 A	250 V	Dca	0.75 mm²	3.5 x 5.7 mm
EK498.3	Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²	black	3.0 m	2.5 A	250 V	Dca	0.75 mm²	3.5 x 5.7 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION