
# DATASHEET

## Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²







### General data

The UK BS1363A - C7 180° power cable in black from EFB-Elektronik is designed as a practical power cable for use in the UK. With a length of 3.0 m, PVC jacket and compact connector configuration, it is suitable for standard-compliant power connections in various applications.

- Connector 1 as BS1363A with 90° angulation
- Connection 2 as a C7 coupling with 180° angulation
- Black version with a length of 3.0 m for flexible installations

The design with two wires, protective conductors and a design for 250 V and 2.5 A supports reliable use in technical environments. The polyvinyl chloride (PVC) sheath material and the operating temperature range of 0 – 70 °C underline the practical design for common mains connections.

Technical details
- Brand: EFB-Elektronik
- Port 1: BS1363A
- Connector 1 angle: 90°
- Connector 2: C7 coupling 180°
- Connector 2 angle: 180°
- Core Count: 2

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²

- Outer jacket colour: black
- Country suitability: UK
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 2.5 A
- Protective conductor available
- Operating temperature: 0 – 70 °C

| **Technical properties** | |
|---|---|
| Bending radius (dynamic/static) | 57 mm |
| Cable printing | D S N FI OVE KEMA-KEUR IEMMEQU VDE N20050 H03VVH2-F 2x0.75mm@ MSL CE |
| Colour outer sheath | black |
| Connection 1 | BS1363A |
| Connection 2 | C7 plug female 180° |
| Connector 1 angulation | 90 ° |
| Connector 2 angulation | 180 ° |
| Country suitability | UK |
| Halogen free | False |
| Locking mechanism | False |
| Material outer sheath | Polyvinylchlorid (PVC) |
| Max. mating cycles | 10000 |
| Nominal voltage | 250 V |
| Number of cores | 2 |
| Oil resistant (acc. EN 60811-2-1) | False |
| Oil resistant (according to EN 60811-404) | False |
| Operating temperature | 0 – 70 °C |
| Protective conductor | True |
| Scope of delivery | Power cord |
| Security certificates | VDE |
| Spiralized cable | False |
| Storage Temperature | -10 – 80 °C |
| Tensile strength (short/long) | mm |
| Type of packaging | Labeled polybag |
| Warranty | 24 month |
| With cord switch | False |

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²

**Available variants**

| ArtNr. | Bezeichnung | Colour outer sheath | Length | Nominal current | Nominal voltage | Reaction-to-fire class according to EN 13501-6 | Nominal cross section conductor | Outer diameter approx. |
|---|---|---|---|---|---|---|---|---|
| EK498.1,8 | Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm² | black | 1.8 m | 2.5 A | 250 V | Dca | 0.75 mm² | 3.5 x 5.7 mm |
| EK498.3 | Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm² | black | 3.0 m | 2.5 A | 250 V | Dca | 0.75 mm² | 3.5 x 5.7 mm |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION