

DATASHEET

Power Cable UK BS1363A - C5 180°, Black, 1.8 m, 3 x 0.75 mm²



General data

The UK BS1363A - C5 180° power cable, black from EFB-Elektronik is designed as a 1.8 m long power cable for use in the UK. With BS1363A connection in 90° angulation and C5 cloverleaf coupling with 180° angle, it is suitable for standard-compliant power connections in technical and practical applications.

- Black outer jacket color for unobtrusive integration
- Equipped with BS1363A and C5 cloverleaf coupling

The three-wire design with protective conductor supports a safe energy supply at a nominal voltage of 250 V and a nominal current of 2.5 A. The polyvinyl chloride (PVC) jacket material ensures robust, practical cable routing, while the operating temperature range of 0 to 70 °C covers use in typical technical environments.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Port 1: BS1363A
- Connector 1 angle: 90°
- Port 2: C5 cloverleaf coupling
- Connector 2 angle: 180°
- Outer jacket colour: black

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C5 180°, Black, 1.8 m, 3 x 0.75 mm²

- Operating temperature: 0 – 70 °C
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 2.5 A
- Protective conductor available
- Country suitability: UK

Technical properties

Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm ² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	C5 Mickey Mouse female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C5 180°, Black, 1.8 m, 3 x 0.75 mm²

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK499.1,8	Power Cable UK BS1363A - C5 180°, Black, 1.8 m, 3 x 0.75 mm ²	black	1.8 m	2.5 A	250 V	Dca	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

