

DATASHEET

Power Cable UK BS1363A - C5 180°, Black, 3.0 m, 3 x 0.75 mm²



General data

2.5 A / 250 V with fuse 3 A
Suitable for UK, Ireland, Singapur, Malaysia

Technical properties

Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm ² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	C5 Mickey Mouse female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C5 180°, Black, 3.0 m, 3 x 0.75 mm²

Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 - 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 - 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal cross section conductor	Outer diameter approx.
EK499.3	Power Cable UK BS1363A - C5 180°, Black, 3.0 m, 3 x 0.75 mm ²	black	3.0 m	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

