


DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm²



General data

The UK BS1363A to C13 power cable from EFB-Elektronik is designed as a 2.0 m long connection cable for use in the United Kingdom. With a black outer sheath, 3 wires and protective conductor, it is suitable for standard-compliant power supplies in technical applications with a custom-fit device connection.

- Connector 1 as BS1363A with 90° angulation
- Connection 2 as a straight IEC socket with 180° angulation
- 2.0 m long power cable in black PVC design with protective conductor

The polyvinyl chloride jacket supports a robust and practical design for operation in the temperature range from 0 to 70 °C. With a nominal voltage of 250 V and a nominal current of 10 A, the cable is designed for common supply tasks; its suitability for the UK market makes it easier to use in appropriate system environments.

Technical details

- Brand: EFB-Elektronik
- Number of wires: 3
- Port 1: BS1363A
- Connector 1 angle: 90°
- Connection 2: IEC socket straight

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm²

- Connector 2 angle: 180°
- Outer jacket colour: black
- Operating temperature: 0 – 70 °C
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: UK

Technical properties	
Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm ² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK500.2	Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	2.0 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK500.3	Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm
EK500.5	Power Cable UK BS1363A - C13 180°, Black, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

