


DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 2 m, 3 x 0.75 mm²



General data

The power cable protective contact 90° - C13 180°, grey from EFB-Elektronik is designed for a standard-compliant power supply in European applications. With a right-angled safety plug (type F), straight IEC socket and a length of 2.0 m, it is suitable for compact installations and clean cable routing.

- Safety plug (type F) right-angled and IEC socket straight
- Suitable for Europe and designed with protective conductor

The three-pole structure with polyvinyl chloride (PVC) sheath supports practical and robust cable routing. With a nominal voltage of 250 V and a nominal current of 10 A, the mains cable is designed for typical device connections. The combination of port 1 with 90° angulation and port 2 with 180° angle makes it easier to integrate into confined installation situations.

Technical details

- Type: Power cable protective contact 90° - C13 180°, grey
- Brand: EFB-Elektronik
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight

This datasheet was created automatically on 23-10-2026 . Technical changes reserved.

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 2 m, 3 x 0.75 mm²

- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: grey
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe

Technical properties

Cable printing	VDE H05VV-F 3G1.0mm ² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	grey
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
--------	-------------	---------------------	----------------------	--------	-----------------	-----------------	---------------------------	---------------------------------	------------------------

This datasheet was created automatically on 23-10-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 2 m, 3 x 0.75 mm²

EK501.2,5V2	Power Cable CEE7/7 90° - C13 180°, Grey, 2.5 m, 3 x 1.00 mm ²	grey	IP20	2.5 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm
EK501.2V2	Power Cable CEE7/7 90° - C13 180°, Grey, 2 m, 3 x 0.75 mm ²	grey	IP20	2.0 m	10 A	250 V	Ja	0.75 mm ²	6.5 mm
EK501.3V2	Power Cable CEE7/7 90° - C13 180°, Grey, 3 m, 3 x 1.00 mm ²	grey	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm
EK501.5V2	Power Cable CEE7/7 90° - C13 180°, Grey, 5 m, 3 x 1.00 mm ²	grey	IP20	5.0 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-10-2026 . Technical changes reserved.

