

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 5 m, 3 x 1.00 mm²







General data

The power cable protective contact 90° - C13 180° grey from EFB-Elektronik is designed for standard-compliant power connections in the European environment. With a right-angled safety plug and straight IEC socket, it is suitable for compact connections and clean cable routing in a wide range of applications.

- 5.0 m cable length for flexible installation
- Safety plug (type F) with 90° angulation and IEC socket with 180° connection
- Grey version with protective conductor for practical mains connections

The three-pole structure with protective conductor and the polyvinyl chloride sheath support a robust and at the same time practical design. With a nominal voltage of 250 V and a nominal current of 10 A, the power line is designed for standardised supply connections and is intended for use in Europe.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 5 m, 3 x 1.00 mm²

- Connector 2 angle: 180°
- Outer jacket colour: grey
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe

Technical properties

Cable printing	VDE H05VV-F 3G1.0mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	grey
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Grey, 5 m, 3 x 1.00 mm²

EK501.2V2	Power Cable CEE7/7 90° - C13 180°, Grey, 2 m, 3 x 0.75 mm²	grey	IP20	2.0 m	10 A	250 V	Ja	0.75 mm²	6.5 mm
EK501.3V2	Power Cable CEE7/7 90° - C13 180°, Grey, 3 m, 3 x 1.00 mm²	grey	IP20	3.0 m	10 A	250 V	Ja	1.0 mm²	7.0 mm
EK501.5V2	Power Cable CEE7/7 90° - C13 180°, Grey, 5 m, 3 x 1.00 mm²	grey	IP20	5.0 m	10 A	250 V	Ja	1.0 mm²	7.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION