DATASHEET

Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm²



General data

The C14 180° - C13 180° black IEC extension from EFB-Elektronik is designed as a compact connection solution for standard-compliant power connections. With a length of 0.5 m, black outer jacket colour and a European version, it is suitable for technical applications where short and clean connections are required.

- Compact IEC extension with a length of 0.5 m
- 180° connection design with IEC plug and IEC socket
- Black version with protective conductor for use in Europe

The 3-wire structure with protective conductor supports safe energy transfer at 250 V nominal voltage and 10 A nominal current. The polyvinyl chloride (PVC) sheath material ensures a robust and practical design, while the operating temperature range of 0 to 70 °C covers use in typical technical environments.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: IEC plug
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: black
- Operating temperature: 0 – 70 °C
- Country suitability: Europe
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm²

Technical properties	
Bending radius (dynamic/static)	68 mm
Cable printing	(UL) SVT 3/C 18AWG(0.824mm²) VW-1 75°C 300V E204978 CSA SVT 3/C 0.824MM² (18AWG) FT2 60°C 300V 204790
Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm²

EK503.0,5	Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm²	black	0.5 m	10 A	250 V	Dca	0.75 mm²	6.8 mm
EK503.1	Extension Cable C14 180° - C13 180°, Black, 1.0 m, 3 x 0.75 mm²	black	1.0 m	10 A	250 V	Dca	0.75 mm²	6.8 mm
EK503.2	Extension Cable C14 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm²	black	2.0 m	10 A	250 V	Dca	0.75 mm²	6.8 mm
EK503.3	Extension Cable C14 180° - C13 180°, Black, 3.0 m, 3 x 1.00 mm²	black	3.0 m	10 A	250 V	Dca	1.0 mm²	7.1 mm
EK503.5	Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm²	black	5.0 m	10 A	250 V	Dca	1.0 mm²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION