

DATASHEET

Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm²



General data

The C14 180° - C13 180° black IEC extension from EFB-Elektronik is designed as a standard-compliant extension for IEC interfaces. With a black outer jacket and a length of 5.0 m, it is suitable for flexible installations in different technical environments.

- Black finish for unobtrusive integration
- 5.0 m cable length for flexible installation
- IEC plug 180° and IEC socket straight for precisely fitting connections

The 3-wire structure with protective conductor is designed for use in Europe and combines a nominal voltage of 250 V with a nominal current of 10 A. The polyvinyl chloride (PVC) sheath material supports a practical design for typical applications in the field of cold equipment supply. The operating temperature range of 0 to 70 °C describes the intended use in the usual technical environment.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: IEC plug
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: black
- Operating temperature: 0 - 70 °C
- Country suitability: Europe
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm²

- Protective conductor available

Technical properties	
Bending radius (dynamic/static)	68 mm
Cable printing	(UL) SVT 3/C 18AWG(0.824mm ²) VW-1 75°C 300V E204978 CSA SVT 3/C 0.824MM ² (18AWG) FT2 60°C 300V 204790
Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants								
ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm²

EK503.0,5	Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm ²	black	0.5 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK503.1	Extension Cable C14 180° - C13 180°, Black, 1.0 m, 3 x 0.75 mm ²	black	1.0 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK503.2	Extension Cable C14 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	2.0 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK503.3	Extension Cable C14 180° - C13 180°, Black, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm
EK503.5	Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

