


DATASHEET

Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm²



General data

The power cable protective contact 90° - C13 180° in black version from EFB-Elektronik is designed for standard-compliant power connections in European applications. With a right-angled safety plug and straight IEC socket, it combines a compact connection guide with a practical cable solution for common device connections.

- Safety plug (type F) with 90° angulation for space-saving connections
- IEC socket straight with 180° connection for classic appliance connections
- Black power cable with a length of 2.0 m for use in Europe

The three-pole structure with protective conductor and the PVC sheath support a robust design suitable for everyday use. With a nominal voltage of 250 V and a nominal current of 10 A, the cable is designed for typical standard applications in the power supply sector. The combination of a right-angle connection on the connector side and a straight design on the socket side facilitates integration in confined installation situations.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm²

Technical properties	
Cable printing	VDE H05VV-F 3G0.75mm ² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants								
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.
EK504.0,5V2	Power Cable CEE7/7 90° - C13 180° Black 0.5 m, 3 x 0.75 mm ²	black	IP20	0.5 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.0,75V2	Power Cable CEE7/7 90° - C13 180° Black 0.75 m, 3 x 0.75 mm ²	black	IP20	0.75 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.1V2	Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm ²	black	IP20	1.0 m	10 A	250 V	0.75 mm ²	6.5 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm²

EK504.2V2	Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm ²	black	IP20	2.0 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.3V2	Power Cable CEE7/7 90° - C13 180°, Black 3.0 m, 3 x 1.00 mm ²	black	IP20	3.0 m	10 A	250 V	1.0 mm ²	7.0 mm
EK504.5V2	Power Cable CEE7/7 90° - C13 180°, Black 5.0 m, 3 x 1.00 mm ²	black	IP20	5.0 m	10 A	250 V	1.0 mm ²	7.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

