

DATASHEET

Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm²



General data

The IEC extension C14 180° - C13 180° grey from EFB-Elektronik is designed for reliable power connections with IEC plug and IEC socket. With a length of 1.8 m, it is suitable for compact installations in European applications where a practical extension with a protective conductor is required.

- Gray design for unobtrusive integration into existing systems
- IEC plug and IEC socket in 180° design
- Rated for 250 V and 10 A at 1.8 m length

The cable design with three wires, PVC sheath and protective conductor supports a robust and technically clean implementation in the field of power supply. The operating temperature range of 0 to 70 °C as well as the country's suitability for Europe take into account typical use in technical environments. The C14 C13 grey IEC extension is therefore designed for standard-oriented and functional use in everyday life.

Technical details

- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: grey
- Core Count: 3
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Operating temperature: 0 - 70 °C
- Country suitability: Europe

Technical properties

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm²

Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	grey
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 - 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 - 80 °C
Tensile strength (short/long)	mm
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK507.1,8	Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm²	grey	1.8 m	10 A	250 V	Dca	0.75 mm²	6.8 mm

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm²

EK507.3	Extension Cable C14 180° - C13 180°, Grey, 3.0 m, 3 x 1.00 mm ²	grey	3.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm
EK507.5	Extension Cable C14 180° - C13 180°, Grey, 5.0 m, 3 x 1.00 mm ²	grey	5.0 m	10 A	250 V	Dca	1.0 mm ²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

