

DATASHEET

Power Cable CEE7/7 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm²



General data

The power cable protective contact 180° - C19 180° in black design from EFB-Elektronik is designed as a 3-wire connection cable for standard-compliant power connections. With safety plug (type F) and IEC socket in 180° design, it is suitable for use in Europe and for compact device connections.

- 3-wire power cable with protective conductor for a reliable power supply
- Black version with a length of 1.8 m for practical installations
- Safety plug (type F) and IEC socket in 180° design

The polyvinyl chloride (PVC) sheath is a robust and practical solution for technical applications with a suitable network interface. With a nominal voltage of 250 V and a nominal current of 16 A, the cable is designed for typical applications in the European environment and supports clean integration into existing systems.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: safety plug (type F), straight
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 16 A
- Protective conductor available
- Country suitability: Europe

This datasheet was created automatically on 17-10-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm²

Technical properties	
Cable printing	VDE H05VV-F 3G1.5mm ² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Plug with protective contact (type F), straight
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT003-B VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-15 - 70
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants								
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.
EK511.1,8	Power Cable CEE7/7 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm ²	black	IP20	1.8 m	16 A	250 V	1.5 mm ²	8.6 mm
EK511.3	Power Cable CEE7/7 180° - C19 180°, Black, 3.0 m, 3 x 1.50 mm ²	black	IP20	3.0 m	16 A	250 V	1.5 mm ²	8.6 mm

Note on Intended Use

This datasheet was created automatically on 17-10-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm²

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-10-2026 . Technical changes reserved.

