DATASHEET

Power Cable Switzerland - C13 180°, Black, 2.0 m, 3 x 0.75 mm²



General data

The Swiss Type 12 – C13 180° power cable from EFB-Elektronik is designed for use in Switzerland and combines a Swiss standard type 12 with an angled IEC socket. With a black outer jacket, 2.0 m length and protective conductor, it offers a standard-compliant and practical solution for reliable power connections.

- Version for Switzerland with connection 1 according to Swiss standard type 12
- Connection 2 as an angled IEC socket with 180° angulation
- Black jacket, 2.0 m length and protective conductor for operational use

Technically, the cable is designed as a 3-core power cable with PVC sheathing. It is intended for 250 V nominal voltage and 10 A nominal current and is therefore suitable for common IEC applications. The combination of Swiss Type 12 connector and C13 connector supports clean integration into systems designed for the Swiss market.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connection 1: Swiss Standard Type 12
- Connector 1 angle: 180°
- Connection 2: Angled IEC socket

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable Switzerland - C13 180°, Black, 2.0 m, 3 x 0.75 mm²

- Connector 2 angle: 180°
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Switzerland

Technical properties	
Cable printing	VDE H05VV-F 3G0.75mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Swiss norm type 12
Connection 2	Cold device plug angled, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Suisse
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	R3-10 +S 250V 10A
Protective conductor	True
Security certificates	S
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable Switzerland - C13 180°, Black, 2.0 m, 3 x 0.75 mm²

EK537.2V3	Power Cable Switzerland - C13 180°, Black, 2.0 m, 3 x 0.75 mm²	black	IP20	2.0 m	10 A	250 V	0.75 mm²	6.5 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION