

# DATASHEET

Power Cable Denmark DPin 90° - C5 180°, Black, 1.8 m, 3 x 0.75 mm<sup>2</sup>



## General data

The power cable Denmark DPin 90° - C5 180°, black from EFB-Elektronik is designed as a connecting cable for use between DK DPin 90° and C5 cloverleaf coupling. With a length of 1.8 m and the black version, it is suitable for compact and practical mains connections in various applications.

- Connection 1 as DK DPin 90° for an angular connection
- Connection 2 as C5 cloverleaf coupling for suitable power supplies
- 1.8 m length with black outer jacket for unobtrusive integration

The polyvinyl chloride (PVC) sheath material supports a robust and at the same time practical design. The 3-wire design with protective conductor maps a common power cable configuration and enables reliable integration into technical applications with corresponding connection requirements.

## Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: DK DPin 90°
- Port 2: C5 cloverleaf coupling
- Outer jacket colour: black

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.



# DATASHEET

## Power Cable Denmark DPin 90° - C5 180°, Black, 1.8 m, 3 x 0.75 mm<sup>2</sup>

- Sheath material: Polyvinyl chloride (PVC)
- Protective conductor available

### Technical properties

|                                           |                          |
|-------------------------------------------|--------------------------|
| Colour outer sheath                       | black                    |
| Connection 1                              | DK DPin 90°              |
| Connection 2                              | C5 Mickey Mouse female   |
| Material outer sheath                     | Polyvinyl chloride (PVC) |
| Nominal voltage                           | 250 V                    |
| Number of cores                           | 3                        |
| Oil resistant (acc. EN 60811-2-1)         | False                    |
| Oil resistant (according to EN 60811-404) | False                    |
| Protective conductor                      | True                     |
| Spiralized cable                          | False                    |
| Type of packaging                         | Labeled polybag          |
| With cord switch                          | False                    |

### Available variants

| ArtNr.    | Bezeichnung                                                                    | Colour outer sheath | Length | Nominal cross section conductor | Outer diameter approx. |
|-----------|--------------------------------------------------------------------------------|---------------------|--------|---------------------------------|------------------------|
| EK540.1,8 | Power Cable Denmark DPin 90° - C5 180°, Black, 1.8 m, 3 x 0.75 mm <sup>2</sup> | black               | 1.8 m  | 0.75 mm <sup>2</sup>            | 6.8 mm                 |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

