

DATASHEET

Power Cable Euro - C7 90° Left/Right, Black, 2.0 m, 2 x 0.75 mm²



General data

The Euro-C7 90° L/R power cable in black version from EFB-Elektronik is designed for the connection of a Euro plug (CEE 7/16) with a C7 coupling in 90° design. With a length of 2.0 m, it is suitable for compact installations and practical connection solutions.

- Black finish for unobtrusive integration
- Connection of Euro plug (CEE 7/16) to C7 coupling 90° l/r

The polyvinyl chloride (PVC) jacket supports a robust and practical design for technical applications. With 2 wires and an existing protective conductor, the cable is designed for a functional power supply with suitable connection geometry.

Technical details

- Brand: EFB-Elektronik
- Core Count: 2
- Connector 1: Euro plug (CEE 7/16)
- Port 2: C7 coupling 90° l/r
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable Euro - C7 90° Left/Right, Black, 2.0 m, 2 x 0.75 mm²

- Protective conductor available

Technical properties

Colour outer sheath	black
Connection 1	EURO plug (CEE 7/16)
Connection 2	C7 plug female 90° l/r
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	2
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal cross section conductor	Outer diameter approx.
EK547.2	Power Cable Euro - C7 90° Left/Right, Black, 2.0 m, 2 x 0.75 mm ²	black	IP20	2.0 m	0.75 mm ²	3.5 x 5.7 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

