
DATASHEET

Power Cable CEE7/7 90° - C5 180°, Black, 5.0 m, 3 x 0.75 mm²



General data

The power cable protective contact 90° - C5 180° in black from EFB-Elektronik is designed as a practical connection cable for use in Europe. With a length of 5.0 m, black design and standard-compliant plug connection, it is suitable for applications where a reliable and space-saving power supply is required.

- Safety plug (type F) in right-angled 90° design
- C5 cloverleaf coupling with straight 180° cable entry
- 5.0 m length, black PVC jacket and protective conductor

The three-pole structure with protective conductor supports safe energy transfer in the low-voltage range for devices with a C5 connection. With a nominal voltage of 250 V and a nominal current of 2.5 A, the cable is designed for typical mains connections. The polyvinyl chloride (PVC) sheath material ensures a robust design suitable for everyday use.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Port 2: C5 cloverleaf coupling
- Connector 2 angle: 180°
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 2.5 A
- Protective conductor available
- Country suitability: Europe

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable CEE7/7 90° - C5 180°, Black, 5.0 m, 3 x 0.75 mm²

Technical properties	
Cable printing	VDE H05VV-F 3G0.75mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	C5 Mickey Mouse female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK552.1,8V2	Power Cable CEE7/7 90° - C5 180°, Black, 1.8 m, 3 x 0.75 mm²	black	IP20	1.8 m	2.5 A	250 V	Ja	0.75 mm²	6.5 mm
EK552.3V2	Power Cable CEE7/7 90° - C5 180°, Black, 3.0 m, 3 x 0.75 mm²	black	IP20	3.0 m	2.5 A	250 V	Ja	0.75 mm²	6.5 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable CEE7/7 90° - C5 180°, Black, 5.0 m, 3 x 0.75 mm²

EK552.5V2	Power Cable CEE7/7 90° - C5 180°, Black, 5.0 m, 3 x 0.75 mm²	black	IP20	5.0 m	2.5 A	250 V	Ja	0.75 mm²	6.5 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION