

DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 1 m,
3 x 1.00 mm²



General data

The warm appliance extension C14 180° - C15 180° from EFB-Elektronik is designed as a connection cable for standard-compliant connections between the IEC plug and the hot appliance socket. With 180° angulation on both sides, 1.0 m length and black outer jacket, it is suitable for compact installations in Europe and the UK.

- 180° connections on both sides for space-saving cable routing
- 1.0 m long warmer extension with black rubber outer jacket
- Designed for 3 wires, with protective conductor and country suitability for Europe and UK

The material rubber supports robust and practical cable routing for technical applications where a secure connection between the IEC plug and the hot appliance socket is required. With a nominal voltage of 250 V and a nominal current of 10 A, the cable is designed for typical applications in the environment of hot appliances. The 180° angulation on both connections makes it easier to integrate into confined installation situations.

Technical details

- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connector 1 angle: 180°
- Connection 2: Warm appliance socket
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: black
- Sheath material: rubber
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe & UK

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm²

Technical properties	
Cable printing	VDE H05RN-F 3G1.0mm ² ZHEJIANG JINTING NUCLEARCABLECO.,LTD www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Hot device plug, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe&UK
Halogen free	No
Locking mechanism	False
Material outer sheath	rubber
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	
Plug imprint	JT-SZ3 ENEC 250V 10A
Protective conductor	True
Security certificates	VDE,ENEC
Spiralized cable	False
Storage Temperature	
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants									
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK585.1V2	Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm ²	black	IP20	1.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm²

EK585.2V2	Warm Device Extension C14 180° - C15 180°, Black, 2 m, 3 x 1.00 mm ²	black	IP20	2.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm
EK585.3V2	Warm Device Extension C14 180° - C15 180°, Black, 3 m, 3 x 1.00 mm ²	black	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

