

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Yellow, 3.0 m, 3 x 1.00 mm²



General data

The power cable protective contact 90° - C13 180°, yellow from EFB-Elektronik is designed as a practical connection cable for European applications. With a right-angled safety plug (type F) and straight IEC socket, it is suitable for compact and standard-compliant power connections in different systems.

- Yellow outer jacket for a highly recognizable finish
- 3.0 m length for flexible installations
- Safety plug (type F) right-angled and IEC socket straight for space-saving connections

The polyvinyl chloride (PVC) sheath supports a robust and at the same time practical cable solution for technical applications. With 3 wires, protective conductor, 250 V nominal voltage and 10 A nominal current, the power cable is designed for use in Europe and covers typical requirements for a standard-compliant power supply.

Technical details

- Brand: EFB-Elektronik
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: yellow
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe

Technical properties

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Yellow, 3.0 m, 3 x 1.00 mm²

Cable printing	VDE H05VV-F 3G1.0mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	yellow
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinyl chloride (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Storage Temperature	
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK588GE.3V2	Power Cable CEE7/7 90° - C13 180°, Yellow, 3.0 m, 3 x 1.00 mm²	yellow	IP20	3.0 m	10 A	250 V	Ja	1.0 mm²	7.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Yellow, 3.0 m, 3 x 1.00 mm²

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.

