

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 1.8 m, 3 x 0.75 mm²



General data

The power cable Protective Contact 90° - C13 180° from EFB-Elektronik is designed for use in Europe and connects a right-angled safety plug (type F) with a straight IEC socket. With a length of 1.8 m and green outer jacket colour, it is suitable for standard-compliant power supplies in compact installations.

- Right-angled safety plug (type F) for space-saving connection routing
- Straight IEC socket for a clean device connection
- 1.8 m length with green outer jacket for use in Europe

The cable is designed as a 3-wire power cable with protective conductor and is specified for 250 V and 10 A. The polyvinyl chloride (PVC) sheath material supports a robust and practical design for typical supply connections. The combination of 90° angulation at port 1 and 180° design at port 2 facilitates integration into confined installation situations.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket color: green
- Country suitability: Europe
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 1.8 m, 3 x 0.75 mm²

Technical properties	
Cable printing	VDE H05VV-F 3G0.75mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	green
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants									
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK588GN.1,8V2	Power Cable CEE7/7 90° - C13 180°, Green, 1.8 m, 3 x 0.75 mm²	green	IP20	1.8 m	10 A	250 V	Ja	0.75 mm²	6.5 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 1.8 m, 3 x 0.75 mm²

EK588GN.3V2	Power Cable CEE7/7 90° - C13 180°, Green, 3.0 m, 3 x 1.00 mm ²	green	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm
-------------	---	-------	------	-------	------	-------	----	---------------------	--------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

