

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 3.0 m, 3 x 1.00 mm²



General data

The power cable protective contact 90° - C13 180°, green from EFB-Elektronik is designed as a practical connection solution for use in Europe. With a length of 3.0 m, a green outer jacket as well as a right-angled safety plug (type F) and a straight IEC socket, it is suitable for standard-compliant connections in various applications.

- 3-core power cable with protective conductor for a safe supply
- Safety plug (type F) in 90° design and IEC socket with 180° angulation
- Nominal voltage 250 V and nominal current 10 A for use in Europe

The cable is designed with a polyvinyl chloride (PVC) sheath and is designed for clear, functional integration into technical systems. The combination of a straight IEC socket, right-angled safety contact connection and 3.0 m cable length supports compact installations with sufficient flexibility.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket color: green
- Country suitability: Europe
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

Technical properties

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 3.0 m, 3 x 1.00 mm²

Cable printing	VDE H05VV-F 3G0.75mm ² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	green
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK588GN.1,8V2	Power Cable CEE7/7 90° - C13 180°, Green, 1.8 m, 3 x 0.75 mm ²	green	IP20	1.8 m	10 A	250 V	Ja	0.75 mm ²	6.5 mm
EK588GN.3V2	Power Cable CEE7/7 90° - C13 180°, Green, 3.0 m, 3 x 1.00 mm ²	green	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, Green, 3.0 m, 3 x 1.00 mm²

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

