


DATASHEET

Extension Cable C20 180° - C19 180°, Black, 3.0 m, 3 x 1.50 mm², IEC Lock

IEC-LOCK



General data

With „IEC Lock“: prevents accidentally removing of the C19 jack from devices

After connecting, the C19 jack only can be released after sliding back the red latch

16 A / 250 V VDE geprüft

Technical properties

Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Halogen free	False
Material outer sheath	PVC
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C20 180° - C19 180°, Black, 3.0 m, 3 x 1.50 mm², IEC Lock

With cord switch ☐ False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal cross section conductor	Outer diameter approx.
EK607SW.1	Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm ² , IEC Lock	black	IP20	1.0 m	1.5 mm ²	8.6 mm
EK607SW.2	Extension Cable C20 180° - C19 180°, Black, 2.0 m, 3 x 1.50 mm ² , IEC Lock	black	IP20	2.0 m	1.5 mm ²	8.6 mm
EK607SW.3	Extension Cable C20 180° - C19 180°, Black, 3.0 m, 3 x 1.50 mm ² , IEC Lock	black	IP20	3.0 m	1.5 mm ²	8.6 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

