# DATASHEET

## Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 3 m



### General data

The Dual-Lock C14 - C13 IEC extension in blue from EFB-Elektronik is designed for standard-compliant power connections and is suitable for flexible use in technical applications. With a length of 3.0 m, it offers a practical scope for the connection between the IEC plug and the straight IEC socket.

- Blue outer jacket color for clear identification
- Version with IEC plug and IEC socket straight
- With a length of 3.0 m and a nominal current of 10 A and a nominal voltage of up to 250 V

The polyvinyl chloride (PVC) sheath supports practical and resilient cable routing in technical environments. The three-pole design with protective conductor creates a suitable solution for applications where a reliable IEC connection is required.

Technical details
- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connection 2: IEC socket straight
- Outer jacket colour: blue
- Core Count: 3
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

### Technical properties

| | |
|---|---|
| Colour outer sheath | blue |
| Connection 1 | Cold device plug (IEC 60320) |
| Connection 2 | Cold device plug straight, female |

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 3 m

| | |
|---|---|
| Halogen free | False |
| Material outer sheath | Polyvinylchlorid (PVC) |
| Nominal voltage | 250 V |
| Number of cores | 3 |
| Oil resistant (acc. EN 60811-2-1) | False |
| Oil resistant (according to EN 60811-404) | False |
| Protective conductor | True |
| Spiralized cable | False |
| Type of packaging | Labeled polybag |
| With cord switch | False |

### Available variants

| ArtNr. | Bezeichnung | Colour outer sheath | Degree of protection | Length | Nominal current | Nominal voltage | With protective conductor | Nominal cross section conductor | Outer diameter approx. |
|---|---|---|---|---|---|---|---|---|---|
| EK620BL.1 | Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 1 m | blue | IP20 | 1.0 m | 10 A | 250 V | Ja | 1.04 mm² | 8.0 mm |
| EK620BL.1,5 | Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 1,5 m | blue | IP20 | 1.5 m | 10 A | 250 V | Ja | 1.04 mm² | 8.0 mm |
| EK620BL.2 | Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 2 m | blue | IP20 | 2.0 m | 10 A | 250 V | Ja | 1.04 mm² | 8.0 mm |
| EK620BL.3 | Extension Cable Dual Lock C14 - C13 IEC Lock, Blue, 3 m | blue | IP20 | 3.0 m | 10 A | 250 V | Ja | 1.04 mm² | 8.0 mm |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION