DATASHEET

Extension Cable C14 - C13, Dual Lock, Red, 1 m







General data

The Dual-Lock C14 - C13 IEC extension in red from EFB-Elektronik is designed for standard-compliant connections in the area of IEC connections. With an IEC plug on a straight IEC socket and a length of 1.0 m, it is suitable for compact installations in a wide range of technical applications.

- Outer jacket color red for clear visual assignment
- Three-pole design with protective conductor
- IEC connection with IEC plug and IEC socket straight

The polyvinyl chloride (PVC) jacket supports a robust and practical design for technical use. With a nominal voltage of up to 250 V and a nominal current of 10 A, the extension is designed for typical supply scenarios in technical systems.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: IEC plug
- Connection 2: IEC socket straight
- Outer jacket colour: red
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: up to 250 V
- Rated current: 10 A

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 - C13, Dual Lock, Red, 1 m

• Protective conductor available

Technical properties	
Colour outer sheath	red
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Halogen free	False
Locking mechanism	True
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK620RT.0,5	Extension Cable C14 - C13, Dual Lock, Red, 0.5 m	red	IP20	0.5 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.1	Extension Cable C14 - C13, Dual Lock, Red, 1 m	red	IP20	1.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.2	Extension Cable C14 - C13, Dual Lock, Red, 2 m	red	IP20	2.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.3	Extension Cable C14 - C13, Dual Lock, Red, 3 m	red	IP20	3.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION