DATASHEET

Extension Cable C14 - C13, Dual Lock, Red, 2 m







General data

The Dual-Lock C14 - C13 IEC extension from EFB-Elektronik in a red version is designed for standard-compliant mains connections with IEC plug and IEC socket. With a length of 2.0 m, it is suitable for applications where a compact and at the same time flexible connection is required.

- Red version for a clear assignment in the body
- 2.0 m length for practical reach
- 3-wire version with protective conductor

The design with IEC plug and straight IEC socket supports a clean connection between C14 and C13 interfaces. The polyvinyl chloride (PVC) sheath provides a practical sheath for technical installations. With a nominal voltage of up to 250 V and a nominal current of 10 A, the extension is designed for corresponding standard applications.

Technical details
- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connection 2: IEC socket straight
- Outer jacket colour: red
- Core Count: 3
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 - C13, Dual Lock, Red, 2 m

- Rated current: 10 A
- Protective conductor available

Technical properties	
Colour outer sheath	red
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Halogen free	False
Locking mechanism	True
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK620RT.0,5	Extension Cable C14 - C13, Dual Lock, Red, 0.5 m	red	IP20	0.5 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.1	Extension Cable C14 - C13, Dual Lock, Red, 1 m	red	IP20	1.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.2	Extension Cable C14 - C13, Dual Lock, Red, 2 m	red	IP20	2.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm
EK620RT.3	Extension Cable C14 - C13, Dual Lock, Red, 3 m	red	IP20	3.0 m	10 A	250 V	Ja	1.04 mm²	8.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION