DATASHEET

Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m







General data

The Dual-Lock C14 - C13 black IEC extension from EFB-Elektronik is designed as a 1.5 m long connection solution for IEC plugs and a straight IEC socket. The black version supports flexible use in technical applications with C14 and C13 connections.

- 1.5 m length for practical device connection
- Version with IEC plug and straight IEC socket
- Rated for 250 V, 10 A and with protective conductor

The three-wire design with a polyvinyl chloride (PVC) jacket supports a robust connection for typical IEC applications. The combination of nominal voltage, nominal current and protective conductor ensures a technically clear design in the area of device supply.

Technical details
- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: IEC plug
- Connection 2: IEC socket straight
- Outer jacket colour: black

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m

- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

Technical properties	
Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Halogen free	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK620SW.0,5	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 0.5 m	black	IP20	0.5 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.1	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1 m	black	IP20	1.0 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.1,5	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m	black	IP20	1.5 m	10 A	250 V	Ja	1.04 mm²	8.0
EK620SW.2	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 2 m	black	IP20	2.0 m	10 A	250 V	Ja	1.04 mm²	8.0

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C14 180° - C13 180°, Dual Lock, Black, 1.5 m

EK620SW.3	Extension Cable C14 180° - C13 180°, Dual Lock, Black, 3 m	black	IP20	3.0 m	10 A	250 V	Ja	1.04 mm²	8.0

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION