

DATASHEET

Warm Device Cable CEE 7/7 90° to C15, Black, 1 m, 3 x 1.00 mm²



General data

The CEE 7/7 90° to C15 180° hot appliance cable from EFB-Elektronik is designed as a practical connection cable for European applications. With a black outer jacket, 1.0 m length and protective conductor, it is suitable for reliable power supplies in technical installations.

- Safety plug (type F) with right-angle design and 90° angulation
- Warm appliance socket with 180° angle for suitable appliance connections
- 3-wire cable with black rubber jacket and 1.0 m cable length

The design with a nominal voltage of 250 V and a nominal current of 10 A supports use on common hot appliance interfaces. The rubber-coated version ensures robust and at the same time application-oriented cable routing, while the suitability for Europe clearly defines the area of application.

Technical details

- Brand: EFB-Elektronik
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: Warm appliance socket
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: black
- Sheath material: rubber
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Europe

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

Warm Device Cable CEE 7/7 90° to C15, Black, 1 m, 3 x 1.00 mm²

Technical properties	
Cable printing	VDE H05RN-F 3G1.0mm ² ZHEJIANG JINTING NUCLEARCABLECO.,LTD www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Hot device plug, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	rubber
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants									
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK625.1V2	Warm Device Cable CEE 7/7 90° to C15, Black, 1 m, 3 x 1.00 mm ²	black	IP20	1.0 m	10 A	250 V	Ja	0.75 mm ²	7.0 mm
EK625.2V2	Warm Device Cable CEE 7/7 90° to C15, Black, 2 m, 3 x 1.00 mm ²	black	IP20	2.0 m	10 A	250 V	Ja	0.75 mm ²	7.0 mm

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

Warm Device Cable CEE 7/7 90° to C15, Black, 1 m, 3 x 1.00 mm²

EK625.3V2	Warm Device Cable CEE 7/7 90° to C15, Black, 3 m, 3 x 1.00 mm ²	black	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.3 mm
-----------	--	-------	------	-------	------	-------	----	---------------------	--------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

