

DATASHEET

10" 1U Socket Strip 4 x CEE 7/3 w/o Switch, in Alu Profile, Grey



General data

10" 1U Socket Strip in Aluminium profile

Outlets 4 x CEE7/3

Outlets turned 45°

With increased personal protection against electric shock

Cable 2.0 m black, H03VV-F 3G 1.5 mm² 250 V / 16 A with angled CEE7/7 plug

Certifications CE, RoHS

Technical properties

Angle rotated central insert	45° °
Colour of power cord	grey
Core cross section	1.50 mm ²
Degree of protection	IP20
Halogen free	False
Housing shape	Rectangular
Length of power cord	2.0 m
Mains filter	False
Material	Metal
Material quality	Aluminium Aluminium
Max. connected load	3500 W
Mounting dimension (standardised)	436 mm
Nominal current	16 A
Nominal voltage	250 V
Number of height units (U)	1 U

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

10" 1U Socket Strip 4 x CEE 7/3 w/o Switch, in Alu Profile, Grey

Number of phases	1
Over voltage protection	False
Packaging	Polybag in cardboard box
Residual current circuit breaker (RCCB)	False
Rotated central insert	True
Scope of delivery	1 x power strip incl. mounting brackets
Surface finishing	Matt
Surface treatment	Anodised
Transparent	False
Type of mains connection	CEE 7/7
With cover lid	False

Available variants

ArtNr.	Bezeichnung	Anti-bacterial treatment	Colour	Compatible with Amazon Alexa	Compatible with Apple HomeKit	Compatible with Google Assistant	IFTTT support available	Number of socket outlets with protective switch contact (CEE7/3)	With on/off switch	Height	RAL-number (similar)
EK631DE.10	10" 1U Socket Strip 4 x CEE 7/3 w/o Switch, in Alu Profile, Black	False	black	False	False	False	False	4	False	45 mm	9005
EK631DE.10GR	10" 1U Socket Strip 4 x CEE 7/3 w/o Switch, in Alu Profile, Grey	False	grey	False	False	False	False	4	False	45 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

