

DATASHEET

19" Rack-mount chassis 2U - 14 slots



General data

Up to 14 converter can be inserted or replaced in running operation (hot-swappable)
 Supports Ethernet, Fast Ethernet, Gigabit, Singlemode and Multimode converter
 Dual power supply for power redundancy
 19"/2U housing (L x W x H): 485 x 231 x 90 mm

Technical properties

Construction type	empty chassis
Depth	231 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Height	90 mm
Layer 2	False
Managed	False
Power over Ethernet	False
Suitable for 19 inch mounting	True
Width	485 mm

Available variants

ArtNr.	Bezeichnung	Unique
ELOCH1	19" Rack-mount chassis 2U - 14 slots	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

DATASHEET

19" Rack-mount chassis 2U - 14 slots

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

