




DATASHEET

19" EFB Server 42U, 800x1000 mm, F=1-Part R=2-Part, RAL7035



General data

The 19" server cabinet of the EFB server series in 800 x 1000 mm, RAL 9005 and 42 U is designed for demanding network and IT environments. It combines high mechanical stability with practical equipment for the structured installation of active and passive components.

- Maximum load capacity up to 1600 kg - Provides high reserves for heavy loading and creates safety for later expansions.
- Perforated steel door at the front and perforated split steel door at the rear - Supports air exchange and facilitates access to the installed technology.
- Baying-compatible design with cable entry over the roof on the left and right and open floor - Simplifies integration into rows of cabinets and keeps cable routing flexible.

The cabinet is designed as a 19" server cabinet in accordance with DIN 41494 and is designed for the mounting levels at the front and rear. The passive ventilation supports thermally non-critical operation, while the floor is open in the

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" EFB Server 42U, 800x1000 mm, F=1-Part R=2-Part, RAL7035

delivery state and modular floor panels can be optionally added. The doors open up to 270 °, and the front door is designed with a replaceable profile half-cylinder in accordance with DIN 18252. Together with the earthing, the powder-coated surface and the IP20 protection class for installed floor panels, a robust solution for professional infrastructure expansion is created.

Technical details

- Number of doors: 2
- Degree of protection: IP20 for installed floor panels
- Type of ventilation: passive
- Floor air intake: Floor open when delivered, modular floor panels optional
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated one-piece steel door
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 5-point rod closure with swing handle
- Rear door locking: 3-point rod closure with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x cage nut set (pack of 20 pieces), 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties

Active air conditioning	False
Air inlet floor	Bottom open when delivered, (modular floor panels optional)
Cabinet Series	EFB-Server
Cable entry roof/floor	Roof left and right across the entire depth of the cabinet, open base
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 with base plates installed
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" EFB Server 42U, 800x1000 mm, F=1-Part R=2-Part, RAL7035

Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 % / 86 % perforated area
Perforation level rear door	> 80 % / 86 % perforated area
Scope of delivery	1x cabinet, 1 x cage nut set (20 pieces per pack), 4 x leveling feet M12, 2 x wrenches
Stackable	True
Surface finishing	Powder coating
Toolless depth adjustment	True
Type of back door	Steel perforated 2-part
Type of front door	Steel perforated 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	False
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width glazed door	With vertical cable management	Height	RAL-number	Number of doors
ESV-4280TS.P1P2OS	19" EFB Server 42U, 800x1000 mm, F=1-Part R=2-Part, RAL7035	black	1000 mm	5-point rod locking mechanism with swivel lever	Steel	Steel	1600 kg	42 HE	3-point rod locking mechanism with swivel lever	800 mm	False	2000 mm	9005	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

