


DATASHEET

19" EFB Server 47U, 800x1000 mm, F+R 1-Part, RAL7035













General data

The 19" server cabinet of the EFB server series in 800 x 1000 mm and RAL 7035 is designed for demanding installations in the network and IT environment. With 47 U, a maximum load capacity of 1600 kg and a completely pre-assembled, bolted frame, it offers a resilient basis for the structured installation of active and passive components.

• 47U and 1600 kg maximum load capacity – Creates reserves for high assembly densities and heavy IT components.
• Perforated steel front and rear doors with passive ventilation – Supports air exchange without active cooling and remains mechanically robust.
• Baying-compatible design with front and rear mounting levels – Makes it easier to expand cabinet rows and simplifies removal.

The design combines offset profile rails with tool-free depth adjustment and practical cable routing. The roof is prepared for feeding on the left and right over the entire cabinet depth. The floor is open when delivered and can be supplemented with modular floor panels if required. The front and rear doors are one-piece and each has an opening

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

19" EFB Server 47U, 800x1000 mm, F+R 1-Part, RAL7035

angle of 270°. The front door can be secured via a replaceable profile half-cylinder in accordance with DIN 18252.

Technical details
- Number of doors: 2
- Degree of protection: IP20 for installed floor panels
- Type of ventilation: passive
- Floor air intake: Floor open when delivered, modular floor panels optional
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated one-piece steel door
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 5-point rod closure with swing handle
- Rear door locking: 5-point rod closure with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x cage nut set (pack of 20 pieces), 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Bottom open when delivered, (modular floor panels optional)
Cabinet Series	EFB-Server
Cable entry roof/floor	Roof left and right across the entire depth of the cabinet, open base
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 with base plates installed
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" EFB Server 47U, 800x1000 mm, F+R 1-Part, RAL7035

Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 % / 86 % perforated area
Perforation level rear door	> 80 % / 86 % perforated area
Scope of delivery	1x cabinet, 1 x cage nut set (20 pieces per pack), 4 x leveling feet M12, 2 x wrenches
Stackable	True
Surface finishing	Powder coating
Toolless depth adjustment	True
Type of back door	Steel perforated 1-part
Type of front door	Steel perforated 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	False
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
ESV-4280GR.P1OS	19" EFB Server 42U, 800x1000 mm, F+R 1-Part, RAL7035	grey	1000 mm	5-point rod locking mechanism with swivel lever	Steel	Steel	1600 kg	42 HE	5-point rod locking mechanism with swivel lever	800 mm	False	False	2000 mm	7035	2
ESV-4780GR.P1OS	19" EFB Server 47U, 800x1000 mm, F+R 1-Part, RAL7035	grey	1000 mm	5-point rod locking mechanism with swivel lever	Steel	Steel	1600 kg	47 U	5-point rod locking mechanism with swivel lever	800 mm	False	False	2200 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION