


DATASHEET

Frame Set 1-port, for keystones, DIN49075, RAL9010



General data

For holding all EFB RJ45 Keystone modules
 Frame set in 1-port or 2-port
 45° slanted outlet
 Outer ring 80x80mm and central plate 50x50mm according to DIN49075
 Separate earthing lead for 6.3mm fast-on connection
 With dust covers and labeling field 12x40mm

Scope of delivery: Keystone frame, outer ring, central plate

Technical properties

Assembly arrangement	Frame set
Connection unit	None
Halogen free	No
Imprintable label	with indication plate
Material	Metal
Mounting method	Flush mounted (plaster)
Receptacle for	Keystone
Support ring	True

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Frame Set 1-port, for keystones, DIN49075, RAL9010

Temperature	0 - 60° °C
Type of fastening	mounting with screw
With dust cover	True
With hinged lid	True
With imprint	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth of device	Height of device	RAL-number (similar)	Suitable for number of connectors	Width of device	With buses/couplings
ET-25085V3	Frame Set 2-port, for keystones, DIN49075, RAL9010	white	24.4 mm	80 mm	9010	2	80 mm	False
ET-25087V3	Frame Set 1-port, for keystones, DIN49075, RAL9010	white	24.4 mm	80 mm	9010	1	80 mm	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

