
DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010















General data

This shielded Cat.6 data socket from EFB-Elektronik in white according to RAL 9010 is designed for flush-mounted installation and can also be used in floor tank and underfloor installations. With two RJ45 connections, slanted outlet direction and compact design, it combines flexible integration with tidy installation in modern network environments.

• Category 6 with 250 MHz bandwidth – Supports transmissions up to 5 Gb and creates reserves for structured network infrastructures.
• Dual shielded RJ45 with LSA connector – Allows for clean termination and contributes to stable signal quality.
• Flush-mounted mounting with cover frame, dust protection, text field and separate cable strain relief – facilitates professional integration and supports clear labelling and safe cable routing in everyday life.

The version is design-ready and has colour coding and a separate earthing connection. The shield connection is made

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010

via a screw. The supply cable for laying cables can be routed at the top or bottom. With its compact dimensions of 50 mm width, 50 mm height and 40.95 mm depth as well as protection class IP20, the data socket is suitable for structured cabling indoors.

Technical details
- Brand: EFB-Elektronik
- Category: 6
- Bandwidth: 250 MHz
- Transmission: 1 Gb, 2.5 Gb, 5 Gb
- Connector type: RJ45 2x8(8)
- Connection type: LSA
- With bushings/couplings: Yes
- Suitable for number of bushings/couplings: 2
- Sockets shielded: Yes
- Colour: white
- RAL number: 9010
- Mounting type shield connection: Screw
- Flush-mounted: Yes
- Floor tank/underfloor mounting: Yes
- Cover frame: Yes
- Outlet direction: oblique
- Mounting type: Screws
- With dust cover: Yes
- With text box: Yes
- Colour coding: Yes
- Designable: Yes
- Separate cable strain relief: Yes
- Separate ground connection: Yes
- Degree of protection (IP): IP20
- Installation cable feed: top/bottom
- Device width: 50 mm
- Device height: 50 mm
- Device depth: 40.95 mm

Technical properties	
Bandwidth	250 MHz
Category	6
Centre plate	True
Colour coding	True
Connection type	LSA
Cover frame	True
Degree of protection	IP20

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010

Design suitable	True
Duct installation	True
Floor box/sub-floor mounted	True
Flush mounted (plaster)	True
Mounting method shielding connection	Screw
Outlet direction	Inclined
POE Standard	POE+
RAL-number	9010
Separate earthing connection	True
Separate strain relief	True
Shielded buses	True
Shielded housing	True
Suitable for number of connectors	2
Surface mounting	False
Temperature Range (Operation)	-10 – 60 °C
Transmission	2,5 Gbit
Type of connector	RJ45 2x8(8)
Type of fastening	Screwing
With buses/couplings	True
With dust cover	True
With label space	True

Available variants

ArtNr.	Bezeichnung	Depth of device	Height of device	Supply line for installation cable	Width of device	Colour
ET-25211.1V1	Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010	40.95 mm	50 mm	Up/down	50 mm	white
ET-25211.2V1	Data outlet Cat.6 250MHz, right/left, Flush, 2xRJ45, RAL9010	40.95 mm	50 mm	Left/right	50 mm	white

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION