

# DATASHEET

## 50-Port Fast Ethernet Switch + 2 GE SFP/RJ45 Combo Ports



### General data

50x Fast Ethernet Ports + 2x Gigabit SFP/RJ45 Combo Slots

Full/Half-duplex

Autonegotiation, Auto-MDI/MDIX

19" Mounting brackets included

Metal housing with fan (L x W x D): 440 x 230 x 44 mm

### Technical properties

|                     |          |
|---------------------|----------|
| 10 Gigabit Ethernet | False    |
| Depth               | 230.0 mm |
| Ethernet            | True     |
| Fan                 | True     |
| Fast Ethernet       | True     |
| Gigabit Ethernet    | False    |
| Height              | 44.0 mm  |
| Layer 2             | False    |
| Layer 3             | False    |
| Layer 4             | False    |
| Layer 7             | False    |

This datasheet was created automatically on 28-09-2026 . Technical changes reserved.



# DATASHEET

## 50-Port Fast Ethernet Switch + 2 GE SFP/RJ45 Combo Ports

|                                            |                             |
|--------------------------------------------|-----------------------------|
| Manageable                                 | False                       |
| Manufacturer                               | LevelOne                    |
| Mounting method                            | 482.6 mm (19 inch) mounting |
| Number of combination-ports RJ45/Mini GBIC | 2                           |
| Number of ports 10/100 Mbps RJ45           | 48                          |
| Width                                      | 440.0 mm                    |

### Available variants

| ArtNr.   | Bezeichnung                                              | Unique |
|----------|----------------------------------------------------------|--------|
| FGU-5021 | 50-Port Fast Ethernet Switch + 2 GE SFP/RJ45 Combo Ports | Unique |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 28-09-2026 . Technical changes reserved.

