

# DATASHEET

Dome closure round 525mm high, D=285mm



## General data

Two oval ports for uncut tubes or loop-cable. Eight round ports with each 32mm diameter. Cable entries with mechanical seal at customer choice, see accessories. Splice trays with crimp- or heat splice holder, see accessories.

## Technical properties

|                               |                    |
|-------------------------------|--------------------|
| Colour                        | Black              |
| Degree of protection          | IP68               |
| Direct Burial                 | True               |
| Material                      | Plastic            |
| Operating Temperature         | -40 - 70 °C        |
| Splice Cassette               | without cassette   |
| Splice Holder                 | without            |
| Suitable for number of fibres | 288                |
| Type of closure               | Connecting closure |
| UV resistant                  | True               |

## Available variants

| ArtNr. | Bezeichnung | Unique |
|--------|-------------|--------|
|--------|-------------|--------|

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



# DATASHEET

## Dome closure round 525mm high, D=285mm

|          |                                           |        |
|----------|-------------------------------------------|--------|
| CFOC2-AA | Dome closure flat 380mm high, 290 x 150mm | Unique |
| CFOC2-AB | Dome socket flat 450mm high, 290 x 150mm  | oval   |
| FOC2-CB  | Dome closure round 525mm high, D=285mm    | round  |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

