

DATASHEET

28-Port L2 Managed Gigabit Fiber Switch, 24x 100/1000 SFP, 4x Combo RJ45/SFP



General data

24x 100/1000Mbps SFP Slots
 4x 100/1000Mbps Combo (SFP + RJ45)
 SFP Slots support for MiniGBICs 100-FX, 1000Base-X
 Management: SNMP, WEB, RMON, Telnet and TFTP management
 IPv6, IGMPv3, Multicast, VLAN, QOS, Autonegotiation, Auto MDI/MDIX and more.
 1x RS232 RJ45 Port, Diagnostic led
 19" Bracket included
 Metal housing (L x B x H): 440 x 205 x 44 mm

Technical properties

Depth	205.0 mm
Fast Ethernet	True
Gigabit Ethernet	True
Height	44.0 mm
Layer 2	True
Manageable	True
Manufacturer	CTS
Mounting method	482.6 mm (19 inch) mounting
Number of combination-ports RJ45/Mini GBIC	4
Number of other ports	1
Number of ports 1000 Mbps Mini GBIC	24
Operating Temperature	0 - 50 °C
Width	440.0 mm

Available variants

ArtNr.	Bezeichnung	Unique
FOS-3128	28-Port L2 Managed Gigabit Fiber Switch, 24x 100/1000 SFP, 4x Combo RJ45/SFP	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

28-Port L2 Managed Gigabit Fiber Switch, 24x 100/1000 SFP, 4x Combo RJ45/SFP

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

