

DATASHEET

MiniGBIC MM 1000SX 550m SFP, 850nm 1.25G -20..85°C,
LC



General data

Multirate SFP (mini GBIC) for Gigabit Ethernet and 1 Gbit/s or 2 Gbit/s Fiber Channel to Multimode

Technical Data

Up to 2,125 Gbit/s

Hot-pluggable SFP

Integrated digital diagnostic

850nm VCSEL Laser

LC duplex mating face

Up to 500m over 50/125µm Fiber, 300m over 62,5/125µm Fiber

Metalhousing for good EMC

3,3V power supply

Low power consumption

extended temperature range of -20°C up to 85°C

Applications

1,25 Gbit/s 1000Base-SX Ethernet

Dual Rate 1,063/2,125 Gbit/s FiberChannel

RoHS compliant

Technical properties

Compatible to	Standard
Connector	LC Duplex
Construction type	Mini GBIC
Fiber quality	OM2/OM3
Gigabit Ethernet	True
Mode	Multimode
Protocol	1000BaseSX

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

MiniGBIC MM 1000SX 550m SFP, 850nm 1.25G -20..85°C, LC

Range	550 m
Speed	1000 Mbit/s
Temperature	-20 - 85 °C
Wave length	850 nm

Available variants

ArtNr.	Bezeichnung	Unique
FTLF8519P3BNL	MiniGBIC MM 1000SX 550m SFP, 850nm 1.25G -20..85°C, LC	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

