DATASHEET

MiniGBIC SM 10GBase SFP+, LC/10km



General data

Supports 9.95 to 10.5Gb/s bit rates*
Hot-pluggable SFP+ footprint
DDM Funktion, Digital Diagnostics Monitoring
Maximum link length of 10km over SM fiber
Uncooled 1310nm DFB laser
Duplex LC connector
Built-in digital diagnostic functions
RoHS compliant (lead-free)
Single 3.3V power supply
Temperature range
-5°C to 70°C

APPLICATIONS
10GBASE-LR/LW 10G Ethernet
1200-SM-LL-L 10G Fibre Channel

Technical properties

10 Gigabit Ethernet	True
Compatible to	Standard
Connector	LC Duplex
Construction type	Mini GBIC
Fiber qualitiy	OS2
Mode	Singlemode
Protocol	10GBaseLR
Range	10 km
Speed	10 Gbit/s

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

MiniGBIC SM 10GBase SFP+, LC/10km

Temperature	-5 – 70 °C
Wave length	1310 nm

Available variants

ArtNr.	Bezeichnung	Unique
FTLX1471D3BCL	MiniGBIC SM 10GBase SFP+, LC/10km	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION