

DATASHEET

MiniGBIC SM 10GBase SFP+, LC/10km



General data

Supports 9.95 to 10.5Gb/s bit rates*
 Hot-pluggable SFP+ footprint
 DDM Funktion, Digital Diagnostics Monitoring
 Maximum link length of 10km over SM fiber
 Uncooled 1310nm DFB laser
 Duplex LC connector
 Built-in digital diagnostic functions
 RoHS compliant (lead-free)
 Single 3.3V power supply
 Temperature range
 -5°C to 70°C

APPLICATIONS

10GBASE-LR/LW 10G Ethernet
 1200-SM-LL-L 10G Fibre Channel

Technical properties

10 Gigabit Ethernet	True
Compatible to	Standard
Connector	LC Duplex
Construction type	Mini GBIC
Fiber quality	OS2
Mode	Singlemode
Protocol	10GBaseLR
Range	10 km
Speed	10 Gbit/s

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.



DATASHEET

MiniGBIC SM 10GBase SFP+, LC/10km

Temperature	-5 - 70 °C
Wave length	1310 nm

Available variants

ArtNr.	Bezeichnung	Unique
FTLX1471D3BCL	MiniGBIC SM 10GBase SFP+, LC/10km	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.

