


DATASHEET

FTTH 19" 1U Subrack for 8x Module FTTH-MODUL-X incl. cable management



General data

19" subrack for FTTH-MODUL-XX (delivery without modules)
Up to 96 LC ports to 1 unit
with front-sided cable tray
delivery without modules

Technical properties

Degree of protection	IP20
Depth	190.0 mm
Height	44.5 mm
Surface finishing	Powder coating
Type of enclosure	Open
Width	483 mm
With ventilation slots	True
max. Modules	8
max. Ports	96 LC / 48 SC

Available variants

ArtNr.	Bezeichnung	Colour	Material	RAL-number
FTTH-BGT-1HE	FTTH 19" 1U Subrack for 8x Module FTTH-MODUL-X incl. cable management	grey	Steel	7035

Note on Intended Use

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

FTTH 19" 1U Subrack for 8x Module FTTH-MODUL-X incl. cable management

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

