


DATASHEET

FTTH 19" 3U Subrack for 17x Moduk FTTH-MODUL-X incl. cable management







General data

19“ subrack for FTTH-MODUL-XX (delivery without modules)
Up to 204 LC ports to 3 units
with front-sided cable tray
delivery without modules

Technical properties

Degree of protection	IP20
Depth	190.0 mm
Height	135 mm
Surface finishing	Powder coating
Type of enclosure	Open
Width	483 mm
With ventilation slots	True
max. Modules	17
max. Ports	204 LC / 102 SC

Available variants

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

FTTH 19" 3U Subrack for 17x Moduk FTTH-MODUL-X incl. cable management

ArtNr.	Bezeichnung	Colour	Material	RAL-number
FTTH-BGT-3HE	FTTH 19" 3U Subrack for 17x Moduk FTTH-MODUL-X incl. cable management	grey	Steel	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION