

DATASHEET

FTTH Indoor DIN RAIL Box for 4fiber, 4adapter and Fiber overlength box



General data

Application:

Optical Telecommunication Networks
LAN, Optical fiber Communication Network
CATV Networks
FTTH access Network
PON, G-PON

Delivery unassembled (4x shrink protection, material for wall- and din rail mounting included)

When using crimp splice protection, please note that these cannot be firmly inserted

Use only flangeless adapters

Technical properties

Cable sheath support	False
Colour	white
Dimensions	101 x 81 x 29 mm
Foreign body and contact protection	Protection against medium-sized foreign bodies
Hinged splice cassette	True
Holder for gas blocker	False
Holder for splitter	False

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

DATASHEET

FTTH Indoor DIN RAIL Box for 4fiber, 4adapter and Fiber overlength box

IP Protection	IP20
Material	Plastic
Max. Assembly (Adapter)	4
Mounting method	Wall mounting
Number of Fibres	4
Operating Temperature	0 – 50 °C
Possibility of mast mounting	False
Scope of application	Indoor
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Type of Splice protection	Thermo
Water protection	Without protection
With Fiber overlength cassette	True

Available variants

ArtNr.	Bezeichnung	Access Control
FTTH-BOX-IN-5	FTTH Indoor DIN RAIL Box for 4fiber, 4adapter and Fiber overlength box	Without

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.