


DATASHEET

FTTH IP65 Connectionbox for 16fiber, 8adapter and Fiber overlength box



General data

Application:

Optical Telecommunication Networks
 LAN, Optical fiber Communication Network
 CATV Networks
 FTTH access Network
 PON, G-PON

Configuration in LC with duplex adapters for 16 ports/ fibers

Configuration in SC with simplex adapters for 8 ports/ fibers

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

DATASHEET

FTTH IP65 Connectionbox for 16fiber, 8adapter and Fiber overlength box

Delivery unassembled (**Crimp splice holder (12 splices)**, shrink splice holder (max. 16 splices double layed), 8x shrink protection and material for wall mounting included)

Technical properties	
Cable entry with cable gland	2x PG13.5
Cable entry without cable gland	8x max. 3mm / 1x max. 9mm
Cable sheath support	True
Colour	white
Dimensions	213x163x47 mm
Foreign body and contact protection	Protection against ingrees of dust
Hinged splice cassette	True
Holder for gas blocker	False
Holder for splitter	True
IP Protection	IP65
Material	Plastic
Max. Assembly (Adapter)	8
Mounting method	Wall mounting
Number of Fibres	16
Operating Temperature	-25 - 70 °C
Possibility of mast mounting	True
Scope of application	Outdoor
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Type of Splice protection	Crimp & Thermo
UV-resistant	True
Water protection	Protection against jet water
With Fiber overlength cassette	True

Available variants		
ArtNr.	Bezeichnung	Access Control
FTTH-BOX-OUT-2	FTTH IP65 Connectionbox for 16fiber, 8adapter and Fiber overlength box	Special screw/ Seal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

